
CRYST ΜΔ (> LIGHTING THE WAY FOR SIXTY YEARS



ASSEMBLY INSTRUCTION MODEL#XAV-B9306-VG-WH





All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.





You will need 6-Medium Base Bulb 40 Watts Recommended 60 Watts Max. USE LED BULBS FOR EXTENDED USE This fixture is Damp rated

How to install

- 1. Determine the preferred hanging height and adjust to the required rods.
- 2. Feed the wires through the rods and connect them together.
- 3. Slip collar ring and canopy over the rod assembly.
- 4. Slip mounting strap with swivel along wire and thread it into the top of the rod assembly.
- 5. Raise fixture up and attach mounting strap to the outlet box using two outlet box screws.
- 6. Change last sentence to slide collar ride up to canopy and thread it onto the screw collar, securing the canopy.
- 7. Install the metal shade onto the socket.
- 8. Install the bulb(not included) into the socket.

ROD 2 59-3/4" COUPLING 3-1/2" 14-7/8" 5-3/8" Л 6′′ 46''

5

ROD 1

3/4"

]1Pc

0

0

6″

12″

ROD 1 = ■□□

ROD 2=

]3Pcs

WARNING: This product can expose you to Lead which is known to the state of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov





ASSEMBLY INSTRUCTION MODEL#XAV-B9306-VG-WH

Part Number

- Part Numbers
- A. (1)-Mounting hardware
- B. (1)-Canopy W5"xH3/4" #XRF9302VGCAN5IN
- C. (1)-Collar ring
- D. (1)-Rod D1/2"xL6" #XRF9302VGROD6IN
- E. (3)-Rod D1/2"xL12" #XRF9302VGROD12IN
- F. (6)-Metal shade #XRF8321WHSHA6IN
- G. (6)-Socket

