RIC

Collection:Phineas

Installation manual for:

LD7008BR W18"*H8.4"*E5.8"L2

Installation instructions:

- l. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 2. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 3. "E" wire from the fixture is attaced to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 4.Secure mounting bracket to the junction box.

 5.Insert screws (P2) in side of top unit the mounting bracket(P1).
- screw (P3) 6.Lock the lamp body on the mounting bracket (P1) on the wall with a flat head
- 7.Hang Crystal(P11) 8.Install E12 light source.(Bulbs not supplied)

The end!

PARTS LIST

Junction box													
P3 P4 P5 P6 P2 P7 P8 P9 P11 P11 P11												Part	
								0	1		(0)	Picture	
	Octagonal beads	Flat iron frame (L3.94**\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	E12 card type full tooth lamp head	Anti-edge light cup (Φ1.57"**H1.57")	Cylindrical iron (Φ0.55"*#10.31")	Square tube (0.59 ^{me} 1.18 ^{me} T1.0 ^e L15.55 ^m mm)	Double head tube (@0.37*L3.03")	Square box (L4. 8"*\\$4. 8"*\\$40. 8)	Flat head Screw	Mounting bracket screw	U-shaped hanging board (L4.53"*W4.33"*H0.59"mm)	Description	
	48	2	N	ъ	4	1	2	1	4	2	-	Q y	
												Check list	

[&]quot;L" = Hot wire
"N" = Neutral wire
"E" = Ground wire