

Collection:Resolute

Installation manual for: LD4061D38 L38.2"W11"H10.8"L5

## Installation instructions:

- 1. Using the screw (P5) secure the mounting bracket (P4) to the junction box.
- 2.. Connect the chain (P11) to canopy plat (P7) then hanging the lamp body.
- 3. Power cord pass through the chain (P11), canopy plat (P7) and clasp(P6).
- 4. Black wire from ceiling(junction box) attaches to "L"wire from the fixture.
- 5. White wire from ceiling(junction box) attaches to "N"wire from the fixture.
- 6. "E" wire from the fixture is attached to the mounting bracket and an additional "E" wire from the mounting bracket must be secured to the junction box.
- 7.M5 screw (P3)pass through the holes in canopy plate and tighten by nut (P9).
- 8.Install the bulb(not included) in lamp holder (P18).

PARTS LIST

P1 P2 P3 P4 P5 P6 P7 P8 P9 P10 P11 P12 P13	Junction b		"L""""""""""""""""""""""""""""""""""""	
P14 P15 P16 P17 P18				

part	picture	Description	Qty	Check li	st
P1		L7.9" Mounting bracket	1		
P2		M5 Nut	2		
Р3		M5 Screw	2		
P4	(c)	<b>∅</b> 4.0″ Mounting bracket	1		
P5	-	5/32-32 Screw	2		
P6	<b>∞</b>	Clasp	1		
P7		L13.8" Canopy plat	1		
Р8		Loop	4		
Р9	•	Nut	2		
P10	0	Quick link	4		
P11		L59"CHAIN04	2		
P12	Q	Power Cord 6.5' SPT-1 18# black	1		
P13	•	Screw	2		
P14		L21.7"Metal arm	1		
P15	Ħ	0.8"*0.8" Sealing cover	2		
P16		L38. 2"Lampshade	1		
P17		E26 Lamp cup	5		
P18	Î	E26 Lamp holder	5		

L'' = Hot wire

The end!

"N" = Neutral wire
"E" = Ground wire