QUICK REFERENCE GUIDE > RGV3-305-N

Gas Range, 30", 5 Burners

Series 7 | Professional

Stainless Steel | Natural gas



Professional style and performance, with high power burners delivering high heat or the most gentle simmer.

- Top burner heat of 23,500 BTU, for seriously fast boiling
- · Gas oven with 4.6 cu ft total capacity
- Non-tip full-extension shelves in main cavitiy for safe removal of hot dishes
- Made from quality materials and real stainless steel

DIMENSIONS

Height	$35^{3}/_{4} - 36^{3}/_{4}$
Width	29 ⁷ / ₈ "
Depth	29 ¹ / ₈ ′

FEATURES & BENEFITS

Cooktop power

Sealed Dual Flow Burners™ deliver cooktop power up to 22,500 BTU for seriously fast boiling right down to a precise 140°F full surface simmer with the gentlest of flames.

Cooking flexibility

<>

Design quality

This range has craftsmanship in every detail, with real stainless steel, cast-iron trivets, and titanium coated dials. Each cavity features incandescent lights and full extension telescopic racks. From the robust legs to the powerful cooktop, the Range is built to last.

Easy to clean

<>

Total control

Precise control across high and low settings is delivered through the halo-illuminated cooktop dials.

SPECIFICATIONS

Accessories

Square handle option AH-R30

Capacity

Shelf positions 5

Total capacity 4.6 cu ft

Usable capacity	3.4 cu ft
-----------------	-----------

Cleaning

Easy clean porcelain basepan

Controls

Star K Certification

Titanium coated, illuminated

Gas requirements

Metal illuminated dials

Fitting and pipe ½ NPT, min. 5/1 ⅓ flex line

Supply Pressure (natural gas) 6" to 9" W.C

Oven features

Broil pan

Electronic oven control

Full extension telescopic

Infrared Broiler

Internal light

Oven functions

Bake
Broil
Convection bake
Number of functions
Slow cook

Oven performance

Bake power 21,000 BTU

QUICK REFERENCE GUIDE > RGV3-305-N Date: 11.02.2021 > 2

Broil power	18,500 BTU
Power requirements	
Amperage	15A
Supply frequency	60Hz
Supply voltage	120V
Product dimensions	
Depth	29 ¹ / ₈ "
Height	35 ³ / ₄ - 36 ³ / ₄ "
Width	29 ⁷ / ₈ "
Rangetop features	
Sealed Dual Flow Burners™	5
Sealed range top	•
Simmer on all burners	140°F
Vent trim included	Flat vent trim
Rangetop Performance	
Max burner power	23,500 BTU
Power back left	18,500 BTU
Power back right	18,500 BTU
Power centre	23,500 BTU
Power front left	18,500 BTU
Power front right	18,500 BTU
Total cooktop power	97,500 BTU
Recommended back guards and ventilation	on

BGRV3-3030H

Combustible situation

!1	
HCB30-6_N (Professional	
•	
•	
2 years	
82006	

TEST The product dimensions and specifications in this page apply to the specific product and model. Under our policy of continuous improvement, these dimensions and specifications may change at any time. You should therefore check with Fisher & Paykel's Customer Care Centre to ensure this page correctly describes the model currently available. ? Fisher & Paykel Appliances Ltd 2020

Other product downloads available at fisherpaykel.com



User Guide



Service & Warranty Booklet



Installation Guide

