

GEBERIT OMEGA60 ACTUATORS

For Omega Concealed Tanks, 2x6 Installations

SPECIFICATIONS

Actuators for concealed tank and carrier system. Actuator flush plates and push buttons shall be glass, zinc die-cast, and plated to guard against scratches. For tile, stone or other hard surfaced walls only. All components shall be compliant with applicable codes and product standards.

FEATURES

- Designed to maintain appearance push after push
- Moving parts are accessible behind actuator flush plate
- · Made of glass, zinc die cast and plated
- Available in a variety of unique combinations of finish/color
- Incorporates water saving possibilities when used with Geberit dual-flush tanks
 1.6 GPF (6 LPF) and 0.8 GPF (3 LPF) or
 1.28 GPF (4.8 LPF) and 0.8 GPF (3 LPF)
- Includes mounting frame and hardware
- Optional cover frame available as needed to cover rough edges or imperfect wall openings.

WARRANTY


• One-year limited warranty.

Dual-Flush Actuators, Omega 2x6 Installation


Style	Material	Finish	Model No.
Omega60	Die Cast	Brushed Chrome	115.081.GH.1
	Glass	White Glass-Aluminum	115.081.Sl.1
		Black Glass-Aluminum	115.081.SJ.1
		Umber Glass-Aluminum	115.081.SQ.1
	Die Cast	Cover frame (when needed) Brushed Chrome	115.086.GH.1
		Cover frame (when needed) Polished Chrome	115 086 21 1

DIMENSIONS

Omega60 Dual-Flush



Omega60 Cover Frame



Products marked with comply with the American Disabilities Act (ADA) when installed per the requirements of the latest ADA Accessibility Guidelines (ADAAG) and/or ICC/ANSI A117.1.



Job Name:	
Date:	Quantity:
Model Specif	ed:
Variations Sp	ecified:
Customer/Wh	nolesaler:
Contractor:	
Architect:	



Geberit 2100 S. Clearwater Drive Des Plaines, IL 60018 USA

P 847-803-7777 F 847-849-1845

www.geberit.us