



#### **PRODUCT DESCRIPTION** SPECIFICATIONS As its name suggests, Hydra is all about water. Like all of our smart Construction: Aluminum fans, it's wet-rated for outdoor use so you can maintain the continuity Blade: 14° Pitch, 120" sweep, extruded aluminum of your décor inside and out. Even with an impressive 120" blade Downrod: 1" O.D. x 6"H included sweep, this epically scaled smart fan moves a massive amount of air Mounting Slope: Up to 30° without consuming much energy, thanks to a powerful DC motor that runs up to 70% more efficient than AC motors. Control it all with our Lead Wire: 80" exclusive Modern Forms app. Available in 80 inches, 96 inches and 120 Hanging Weight: 46 lbs inches. Total Power: 67.5W Standards: ETL/cETL Wet Location listed FEATURES LIGHT KIT PERFORMANCE • 6 fan speeds through both Summer and Winter Modes Light Source: LED Silent DC motor Light Wattage: 23.5W • Optional LED light kit included **Dimming:** Integrated • Includes RF wall control Color Temperature: 3000K (2700K / 3500K options available) • Additional RF wall control for 3, 4-way control sold separately Rated Life: 50,000 Hours • Compatible with Modern Forms app Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE	WIRELESS PERFORMANCE	
Airflow: 13300 cubic ft per minute on high	RF Pairing Distance: Up to 30 ft from fan	
Power: 44 watts on high	Wi-Fi Range: Up to 150 ft*	
Airflow Efficiency: 302 cubic ft per minute per watt		
Revolutions Per Minute: 40 RPMs on high		

### **ORDER NUMBER**

Model	LED Lumens	Delivered Lumens		Housing	Blade
FR-W1805- 120L	2041	1013	BZ TT	Bronze Titanium Silver	Bronze Titanium Silver

#### Example: FR-W1805-120L-BZ

For 2700K add "27"; 3500K add "35" before the finish: FR-W1805-120L27-TT

\*Results may vary based on application and surroundings.



works with the Google Assistant

modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

Modern Forms retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2019

# HYDRA 120" Ceiling Fan

FR-W1805-120L

MODERN FORMS
SMARTFANS

OPTIONAL ACCESSORIES				
RF Wall Control	F-WC	τw	White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
RF Remote Control	F-RC	w	White	Sold separately. Control fan speed and light brightness, and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.
Wi-Fi Touch Panel Wall Control	F-TS	BK WT		Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod	XF-18       1         XF-24       2         XF-36       3         XF-48       4         XF-60       6	2in 8in 4in AS 6in BA 8in BZ 0in CFI 2in DW GB GH GW	<ul> <li>Dark Walnut</li> <li>Gloss Black</li> <li>Graphite</li> <li>Gloss White</li> </ul>	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. Connects two downrods together.
Sloped Ceiling Kit	XF-SCK	ME MV OB SS TT	Matte Black Matte	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - F-WC-WT, RF Remote Control - F-RC-WT, Wi-Fi Touch Panel - F-TS-WT, Downrod - XF-12-BZ, Downrod Coupler - XF-I-BZ, Sloped Ceiling Kit - XF-SCK-DW

## SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11′	10'	9'	
Downrod	72″	60″	48″	36″	24″	18″	12″	
SLOPED CEILING DEGREE CONVERSION CHART								

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

\*\*Carbon Fiber downrods available in 12", 18", 24" and 36"

<code>+Koa</code> downrods available in 12", 18", 24" and 36"

modernforms.com	Headquarters/Eastern Distribution Center	Central Distribution Center	Western Distribution Center
Phone (866) 810.6615	44 Harbor Park Drive	1600 Distribution Ct	1750 Archibald Avenue
Fax (800) 526.2585	Port Washington, NY 11050	Lithia Springs, GA 30122	Ontario, CA 91760

Modern Forms retains the right to modify the design of our products at any time as part of the company's continuous improvement program. APR 2019