
MODERN FORMS SMART FANS





PRODUCT DESCRIPTION

A modern meditation on style and technology, Lotus is the ultimate utility player. Its clean, streamlined look works well with almost any décor, inside or outdoors. And with our Modern Forms app, this smart fan responds to your behavior patterns with optimized schedules that can help cut down on energy use. Engineered with a quiet, energy-efficient DC motor and a powerful LED luminaire, this fan is peak enlightenment.

SPECIFICATIONS

Construction: Aluminum

Blade: 15° Pitch, 54" sweep, ABS

Downrod: 1" O.D. x 4.5"H included

Mounting Slope: Up to 30°

Lead Wire: 80"

Hanging Weight: 15 lbs Total Power: 30W

Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 13W Dimming: Integrated

Color Temperature: 3000K (2700K / 3500K options available)

Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 Compliant

ESTIMATED AIR PERFORMANCE

Airflow: 5575 cubic ft per minute on high

Power: 17 watts on high

Airflow Efficiency: 332 cubic ft per minute per watt **Revolutions Per Minute:** 167 RPMs on high

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft*

ORDER NUMBER

Model	LED	Delivered		Housing	Blade	
	Lumens	Lumens				
FR-W1809-54L	1110	622	BZ MW	Bronze Matte White	Bronze Matte White	
			тт	Titanium Silver	Titanium Silver	

Example: FR-W1809-54L-BZ

For 2700K add "-27"; 3500K add "-35" before the finish: FR-W1809-54L-27-MW

*Results may vary based on application and surroundings.





modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760



OPTIONAL ACCESSORIES									
RF Wall Control	F-WC	F-WC		White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.				
RF Remote Control	F-RC		wt	White	Sold separately. Control fan speed and light brightness and switch between Summer and Winter Modes from up to 50 ft away. Includes easy-to-install cradle and batteries.				
Wi-Fi Touch Panel Wall Control	F-TS		BK WT	Black White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.				
Downrod	XF-12 XF-18 XF-24 XF-36 XF-48 XF-60 XF-72	12in 18in 24in 36in 48in 60in 72in DW	BA BZ CFI	Automotive Silver Brushed Aluminum Bronze Carbon Fiber** Dark Walnut	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.				
Downrod Couplers XF-I		GB GH GW KO	Gloss Black Graphite Gloss White Koa†	Connects two downrods together.					
Sloped Ceiling Kit	XF-SCK		MB MW OB SS TT	Matte Black Matte White Oil Rubbed Bronze Stainless Steel Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.				

Examples: RF Wall Control - F-WC-WT, RF Remote Control - F-RC-WT, Wi-Fi Touch Panel - F-TS-WT, Downrod - XF-12-BZ, Downrod Coupler - XF-I-BZ, Sloped Ceiling Kit - XF-SCK-DW

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13'	12'	11′	10′	9′
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

NOTE: Recommended maximum downrod length of 72" with 80" lead wire

**Carbon Fiber downrods available in 12", 18", 24" and 36"

*Koa downrods available in 12", 18", 24" and 36"

modernforms.com Phone (866) 810.6615 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760