

NATL-5060-12-HWD10

12V Class II Dimmable Hardwire LED Driver (0-10V dimming)

Source: 120-277V Input / 12V Output
60W

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

12V enclosed dimmable driver to be used with Nora Lighting's 12 Volt systems.

FEATURES

- 0-10V dimming
- Conduit access wiring compartment
- Meet Class II output limits
- 12V DC rated output
- Includes 10' power line connector (NATL-10)
- cULus listed enclosure & cULus recognized driver

ELECTRICAL

Input Voltage: 120-277V

Output Voltage: 12VDC

Wattage: 60W

THD: <20%

Power Factor: 0.95

Dimming: 0-10V

Protection: Short circuit, over voltage and over-temperature protection

COMPATIBLE NORA 12V SYSTEMS

LED Drivers are compatible with Nora Lighting's 12V systems

SERIES	DESCRIPTION
NUTP4	12V Standard Tape Light
NUTP6	12V RGB Color Changing Tape Light
NMP-LED	12V Josh Puck Light
NM1-170	12V 1" M1 Series

OPTIONAL ACCESSORIES

NATL-10: 10' Power Line Connector (included)

NATL-30: 30' Power Line Connector


NATL-302W: Power Line Splitter, white cable. Splits power line connector into two separate connections.

LABELS AND LISTINGS

- cULus Listed Enclosure
- cULus Recognized Driver



PRODUCT IMAGES & DIMENSIONS



NATL-5060-12-HWD10

12V Class II Dimmable Hardwire LED Driver
0-10V dimming



NATL-10 / NATL-30

Power Line Connector (10' included)



NATL-302W

Power Line Splitter

12V Class II Dimmable Hardwire LED Driver (0-10V dimming)

Output Voltage / Wattage

NATL-5060-24-HWD10 = 12V Output / 60W

Optional Accessories

Description

NATL-10 = 10' Power Line Connector (included w/each driver)

NATL-30 = 30' Power Line Connector

NATL-302W = Power Line Splitter, White

Example: **NATL-5060-12-HWD10** = 12V 60W Class II Dimmable Hardwire LED Driver (0-10V dimming)