NELOCAC-16R

16" ELO LED Surface Mount Luminaire

Source: 20W LED 2200lm

PRODUCT DESCRIPTION

16" ELO LED Surface Mount is a thin 1" luminaire that mounts easily over a standard or fire rated junction boxes.

FEATURES

- 2200lm / 20W
- 2700K, 3000K or 4000K @ 90+ CRI
- Easily surface mounts over junction box
- · Pendant kit available to suspend luminaire from canopy
- Dimmable with Triac or ELV dimmer
- · 5-year limited warranty

Surface Mount: Steel bracket mounts on junction box and luminaire twist and locks onto steel bracket.

Compatible Junction Boxes:

- 3" and 4" Octagonal
- 4" Square
- 4" Pancake
- · 4" Plastic Round

Pendant Mounting: Pendant kit (ordered separately) can be used to suspend luminaire from canopy.

ELECTRICAL

Input Voltage: 120-277V

Deliverd Lumens / Wattage: 2200lm / 20W Color Temperature: 2700K, 3000K or 4000K

CRI: 90+ CRI

Lifetime: 54,000 Hours @ L70

Operating Temperature: 0°C to 40°C ambient temperature

Dimming: Triac or ELV @ 120V only

Click Here or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

OPTIONAL ACCESSORIES

NELOCAC-16PK = 4' Pendant Kit for 16" ELO

LABELS AND LISTINGS

- cETLus Listed for Damp Location
- ENERGY STAR certified
- FCC Listed
- 5-Year Limited Warranty
- Certified to the high efficacy requirements of California Title 24 JA8-2019
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (A)(1) and 410.16 (C)(1).




















PRODUCT IMAGES & DIMENSIONS



NELOCAC-16R 16" ELO



NELOCAC-16PK 4' Pendant Kit for 16" ELO



16" ELO LED Surface Mount Luminaire			Optional Accessory
Luminaire Size / Lumens / Wattage	CCT / CRI	Finish	Description
NELOCAC-16R = 16" Round / 2200lm / 20W	927 = 2700K / 90+ CRI 930 = 3000K / 90+ CRI 940 = 4000K / 90+ CRI	W = White	NELOCAC-16PKW = 4° Pendant Kit for 16° ELO, White finish

Example: NELOCAC-16R930W = 16" ELO LED Surface Mount Luminaire, 3000K / 90+ CRI, White finish

