

# NFBIC-401AT/25A

## 4" Recessed MR16 GU10 Line Voltage Fire Rated Housing - Two Hour Fire & Sound Dampening Rated

Source: 25W max.  
MR16 GU10

Type

Project

Catalog No.

Notes

### PRODUCT DESCRIPTION

Specification grade fire-rated new construction housing. The double wall fixture incorporates a non-combustible fiber insulation to prevent passage of flames, toxic gases, ignitable gasses into ceiling plenums. cULus listed housing with two-hour fire rated classification. The noncombustible fiber fill also acts as sound deadening material eliminating the transfer of sound between floors. Suitable for commercial, multi-family and residential applications.

### FEATURES

- Rated for direct contact with insulation
- cULus classified Two Hour Fire Rating
- cULus listed for wet location and through branch circuit wiring
- 24-1/2" Bar hangers with captive nails & alignment feet
- Accommodates 1-3/4" maximum ceiling thickness

### CONSTRUCTION

**Plaster Frame:** High quality 0.03" steel die cut one piece frame.

**Housing:** Die formed 20 gauge galvanized steel construction. Housing interior is comprised of a flexible non-combustible insulation.

**Air Flow Restriction:** Housing has factory installed gaskets to restrict airflow from room into ceiling plenum to <2CFM (cubic feet per minute) in accordance with ASTM-283 Air-Tight requirements.

**Junction Box:** Prewired 0.03" thick galvanized steel, contains one 1-1/8", one 1/2", three 7/8" knockouts and four Romex pryouts with strain relief and snap on covers. All leads are #18AWG wire, the ground wire is connected to the bottom, and quick connectors are supplied on all leads. Through branch circuit wiring, (4-in, 4-out).

**Quick Connect Feature:** Housing contains three quick connections that allow insertion of 1/4" standard conductors to be inserted into the connector. Connectors are pre-attached to fixture power, common, and ground circuits.

**Bar Hangers:** Two 13-3/4" to 24-1/2" adjustable bar hangers with captive nails are included on frame. Bar hangers are parallel to junction box, but can be repositioned 90° perpendicular to junction box if desired. "L" Shaped bar hanger foot to align to bottom of construction joist. A T-Bar notch allow for easy installation in a suspended ceiling.

**Installation:** Classified for use in two hour fire rated L500 Series floor-ceiling designs in the UL Fire Resistance Directory. Mark Spacing, number of luminaires not to exceed the ratio, one per 25sq ft of the total ceiling area, with minimum separation of 3ft between luminaires.

### ELECTRICAL

**Voltage:** 120V

**Socket:** Porcelain GU10

**Wattage:** 25W max.

**Lamp Type:** MR16 GU10

**Thermal Protection:** Standard UL thermal protector rated for 135°C is affixed to inner top surface of housing.

### COMPATIBLE TRIMS

Housing is compatible with trims manufactured by Nora Lighting.




NL-410, NL-411, NL-412, NL-413, NL-414, NL-416, NL-418, NL-420, NL-421, NL-422, NL-423, NL-425, NL-426, NL-427, NL-429, NL-432, NL-439, NL-440, NL-445, NL-448, NL-449, NL-450, NL-452, NL-453, NL-463, NL-465, NL-467, NL-468, NL-469, NL-4810, NL-4814, NL-4826, NL-4827, NL-4840, NL-4845, NL-4855, NL-4856, NL-4857, NL-4859, NL-4865

### LABELS AND LISTINGS

- cULus Classified for Two Hour Fire Rating
- cULus Listed for Wet Locations when used with compatible trims
- Meets or exceeds ASTM-283 Air-Tight requirements
- ANSI/UL 263
- ANSI/UL 1598



### PRODUCT IMAGES & DIMENSIONS



## 4" Recessed MR16 GU10 Line Voltage Fire Rated Housing

Catalog No.

NFBIC-401AT/25A = 4" Recessed MR16 GU10 Line Voltage Fire Rated Housing

Example: NFBIC-401AT/25A = 4" Recessed MR16 GU10 Line Voltage Fire Rated Housing