

NL-3325

3" Frosted Dome Lens with Reflector

Type

Project

Catalog No.

Notes

FEATURES

Trim: Precision spun 0.050 aluminum high grade reflector that includes a frosted dome lens. Gimbal ring allows lamp to be mounted on top of the trim and adjustable up to 35°.

Mounting: Trim includes three trim clips that securely mount trim in housing.

COMPATIBLE HOUSINGS

Compatible with Line Voltage and Low Voltage housings. See individual specification sheets for more information.

LAMP

Line Voltage

50W 120V MR16 GU10 Max. (NH-350AT; NHIC-350AT; NHR-354AT)

Low Voltage

Important: Do not use glass lens (provided) when already using lamp with glass cover
50W 12V MR16 (NL-301 Series; NLIC-301 Series; NLR-304 Series; NLR-305 Series)

LABELS AND LISTINGS

cULus Listed for Wet Location when used with compatible housing.



PRODUCT IMAGES AND DIMENSIONS



NL-3325B



NL-3325BZ



NL-3325CO




NL-3325G



NL-3325N



NL-3325W



3" Frosted Dome Lens with Reflector

Catalog No.

- NL-3325B = Frosted Dome Lens with Specular Clear Reflector and Black Metal Ring
- NL-3325BZ = Frosted Dome Lens with Specular Clear Reflector and Bronze Metal Ring
- NL-3325CO = Frosted Dome Lens with Specular Clear Reflector and Copper Metal Ring
- NL-3325G = Frosted Dome Lens with Specular Clear Reflector and Gold Metal Ring
- NL-3325N = Frosted Dome Lens with Specular Clear Reflector and Natural Metal Ring
- NL-3325W = Frosted Dome Lens with Specular Clear Reflector and White Metal Ring

Compatible Housings

Line Voltage

Catalog No.

- NH-350AT = 3" Non-IC Air-Tight New Construction Housing / 50W max.
- NHIC-350AT = 3" IC Air-Tight New Construction Housing / 50W max.
- NHR-354AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Low Voltage

Catalog No.

- NLIC-301AT/1EL = 3" IC Air-Tight New Construction Housing / 50W max.
- NLIC-3010AT/20 = 3" IC Air-Tight New Construction Housing / 20W max.
- NLIC-3010AT/37 = 3" IC Air-Tight New Construction Housing / 37W max.
- NLIC-3010AT = 3" IC Air-Tight New Construction Housing / 50W max.
- NL-301AT/1EL = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NL-3010AT/20 = 3" Non-IC Air-Tight New Const. Housing / 20W max.
- NL-3010AT/37 = 3" Non-IC Air-Tight New Const. Housing / 37W max.
- NL-3010AT = 3" Non-IC Air-Tight New Const. Housing / 50W max.
- NLR-304AT/1EL = 3" Non-IC Air-Tight Remodel Housing / 50W max.
- NLR-3040AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.
- NLR-3040AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.
- NLR-3040AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.
- NLR-305AT/20 = 3" Non-IC Air-Tight Remodel Housing / 20W max.
- NLR-305AT/37 = 3" Non-IC Air-Tight Remodel Housing / 37W max.
- NLR-305AT = 3" Non-IC Air-Tight Remodel Housing / 50W max.

Example: NL-3325BZ = 3" Frosted Dome Lens with Specular Clear Reflector and Bronze Metal Ring