

NMRT-1

Flanged Gimbal High Performance LED Multiple Lighting Trim (Housing Required)

Source: 11W to 37W LED

850lm to 3000lm per head

Type

Project

Catalog No.

Notes

PRODUCT DESCRIPTION

A beautiful enclosed steel face plate. Gimbal regressed 1.5 inch for a clean ceiling appearance. Available in 1, 2 and 3 LED linear configurations. Excellent for flexible general lighting in commercial and architectural applications.

CONSTRUCTION

Trim: The aluminum face plate is a flanged seamless stamped metal. Each LED gimbal adjusts independently at 40° with 350° rotation.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing.

Trim Style: Trim is available in two styles; 1-1/2" regressed or flat face. Flat face is only available in white finish.

Finish: Flange is available in silver or white finish. Regressed face is available in black, silver or white finish.

ELECTRICAL

Input Voltage: 120V or 277V

Lumens / Wattage:

L85 = 850lm / 11W; **L12** = 1250lm / 16W;

L20 = 2000lm / 25W; **L30** = 3000lm / 37W

Color Temperature: 2700K, 3000K, 3500K, 4000K

CRI: 90+ CRI

Operating Temp.: 0°C to 45°C ambient temperature

Comfort Dim: Comfort Dim color tunes the temperature from a bright 2700K, to a romantic and comfortable 1800K on a gradual, even curve.

Comfort Dim is available in 4 different lumen levels:

- 850-1250 Lumens for lower ceiling heights in commercial and residential applications.
- 2000 Lumens for light commercial and residential high ceiling applications
- 3000 Lumens for commercial high ceiling applications

Dimming: Triac, ELV or 0-10V dimming

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE LED HOUSING


Catalog No.	Description
NMRG-1	Flanged Gimbal LED Housing

LABELS AND LISTINGS

- cULus Listed for damp locations
- ENERGY STAR certified
- 5-Year Limited Warranty



PRODUCT IMAGES AND DIMENSIONS



Dimensions	Length (A)
1 Head	9-3/4"
2 Head	18"
3 Head	23-3/4"

Flanged Gimbal High Performance LED Multiple Lighting Trim - Housing ordered separately

Face Type	Number of Heads	Lumens / Wattage Per Head	Color Temp.	Face / Flange Finish
NMRT-1 = Regressed Face	1 = One Head	L85 = 850lm / 11W	27 = 2700K	BW = Black / White
NMRT-1F = Flat Face	2 = Two Heads	L12 = 1250lm / 16W	30 = 3000K	SS = Silver / Silver
	3 = Three Heads	L20 = 2000lm / 25W	35 = 3500K	WW = White / White
		L30 = 3000lm / 37W	40 = 4000K	
			CD = Comfort Dim	

Example: **NMRT-12L2030BW** = Two Head Regressed Face Flanged Gimbal High Performance LED Multiple Lighting Trim, 2000lm / 25W per head, 3000K, Black Face / White Flange