

MAGNUM Wall Sconce
3-518-xxx


oxygen

FIXTURE TYPE _____

LOCATION _____

PROJECT _____

DATE _____



-25 Satin Copper



-24 Satin Nickel



-40 Aged Brass

Diffusers:





-1 White Opal Glass



- Matte White Acrylic

- LIGHT SOURCE** 1 x 12.1W LED, 3000K, CRI 90
- LUMINAIRE POWER** 14.7W at 120V
- RATED LIFE** 60000 hr RL
- SELECT COLOR TEMPERATURES** 2700K, 3500K, 4000K
- LUMEN OUTPUT** Delivered: (-1) Glass: 1164 lm (LM-79)
Acrylic: 1077 lm (LM-79)
- INPUT VOLTAGE** 120V to 277V AC, 50/60Hz
- DRIVER OUTPUT** 350mA, 14.7W max power
- DIMMING** TRIAC and ELV dimming at 120V AC;
0-10V dimming, 100% to 1% current output
- CONSTRUCTION** Plated Steel and Acrylic /or Glass
- DIFFUSER/ METAL FINISHES** (-124) White Opal Glass/Satin Nickel
(-125) White Opal Glass/Satin Copper
(-140) White Opal Glass/Aged Brass
(-24) Matte White Acrylic/Satin Nickel
(-25) Matte White Acrylic/Satin Copper
(-40) Matte White Acrylic/Aged Brass
- MOUNTING** 2" x 3" J-Box, 4" Octagonal J-Box,
4" Square J-Box with a single device mud ring
- STANDARDS** UL Dry/Damp listed, ADA Compliant, Conforms to
UL STD 1598, Certified CAN/CSA STD C22.2 No 250.0.



DIMENSIONS

- W:** 4.75"
- H:** 18.75"
- Ext:** 4.00"
- M.C:** 15.38" From top of fixture

Order example for standard fixture:
3-518-124 (x- Voltage - xxx-Sequence # - x-Diffuser - xx-Finish)
3: 120V to 277V
 Order example for optional color temperatures: **3-518-27124**
27: 2700K, **35:** 3500K, **40:** 4000K

