

# 2" INGROUND - SQUARE

## 2052 Honeycomb Louver

# WAC



## LANDSCAPE LIGHTING

Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_



### PRODUCT DESCRIPTION


Landscape 2" recessed inground luminaire for up, down, side light applications.

### FEATURES

- Integrated honeycomb louver for reduced glare
- 30° visual cutoff IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

### SPECIFICATIONS

**Input:** 9 - 15VAC (Transformer is required)  
**Power:** 4.1W / 6.6VA  
**Brightness:** 170 lm  
**Beam Angle:** 25°  
**CRI:** 85  
**Rated Life:** 70,000 hours



### ORDERING NUMBER

		Color Temp		Finish	
<b>2052</b>	Square Honeycomb louver	<b>27</b>	2700K	<b>BS</b>	Bronzed Stainless Steel
		<b>30</b>	3000K	<b>SS</b>	Stainless Steel

### IEC safety Standard

	Walk over	Drive over
Resistance to static load test	Yes (1125lbs)	Yes (4496lbs)
Resistance to torque and shear loads test	N/A	Yes

**2052-30** \_\_\_\_\_

Example: **2052-30SS**

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760

# 2" INGROUND - SQUARE

## 2052 Honeycomb Louver

# WAC

## LANDSCAPE LIGHTING

### Magnetic Transformers



Stainless Steel, 12-15V output,  
IP65 rated, UL 1838 listed  
See transformer spec sheet for  
details and its accessories


**9075-TRN-SS**  
75W Max

**9150-TRN-SS**  
150W Max

**9300-TRN-SS**  
300W Max

**9600-TRN-SS**  
600W Max

### 2" Concrete Pour Kit



For installation in concrete.  
Use with a 4" outdoor rated junction box  
and a trade size 2" schedule 80 PVC pipe

**2000-CON-PVC**

### TESTED MAGNETIC LOW VOLTAGE (MLV) DIMMERS

Luminaire	Dimmer					
	Manufacturer	Family	Model	Power Rating	Range*	Note
<b>2052</b>	Lutron	Diva	DVLV-600	600W	20% - 100%	
		Skylark	SLV-600P	600W	15% - 100%	Best performance
		Skylark	S-10P	1000W		Not recommended

\*Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.

waclighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760