LEAD FREE ACCESSORY FAUCETS



MODEL DESCRIPTION FINISH PART #

VICTORIA SERIES 720 VICTORIA Lead Free Accessory Faucet For Filter

COLD ONLY

Shipping Wt: 5 lbs.

Victorian design · adjustable flow control with 1/4 turn ceramic disc valve for filling pitchers and pots · swivel spout

and pois swiver spout

Certified to NSF/ANSI Standard 61 and California Proposition 65.


Chiller sold separately (see EverCold).

Dimensions:

Height: 8" (9" for J-Spout)
Reach: 7" (6.5" for J-Spout)

Spout Diameter: 1/2" Hole Size Required: 1/2"

VICTORIA J-SPOUT



VICTORIA FOR FILTER

CHROME WI-FA720C-CH

SATIN NICKEL-PVD WI-FA720C-SN

SPECIAL* WI-FA720C-__

*SPECIAL = any sigma finish except precious metal (silver & gold) SEE CUSTOM FINISH INFO FOR EXAMPLES.

Allow 8 to 10 weeks for delivery.

J-SPOUT VICTORIA FOR FILTER



CHROME WI-FA720**J**C-CH

SATIN NICKEL-PVD WI-FA720JC-SN

SPECIAL* WI-FA720**J**C-_

*SPECIAL = any sigma finish except precious metal (silver & gold) SEE CUSTOM FINISH INFO FOR EXAMPLES.

Allow 8 to 10 weeks for delivery.

Please call for pricing on any Finish/Faucet combinations not listed.

A separate air gap is available for reverse osmosis on this model.



VICTORIA
COLD ONLY

Meets National Lead Laws including NSF 372 - 2011 Drinking Water System Components -

MAXIMUM recommended line pressure for this product is 75 PSI. Pressure above 75 PSI indicates the absence of a properly functioning water pressure regulator at the property. Excessive water pressure poses a risk of property damage to you.Problems due to excessive water pressure are NOT covered by this product's warranty. BEFORE inst allation of any Water, Inc. product, confirm that water supply pressure does not exceed 75 PSI. Questions? Contact Water, Inc. Service Depart. at 800.322.WATER(9283) Installations must comply with appropriate plumbing codes. Do not use vinyl tubing to connect any Water, Inc. Product to a water source. Polyethylene tubing is recommended for cold water applications.

FAUCET KIT Part # WI-FAUCET-KIT Shipping Wt: 2 lbs.

8"

Compatible with this Water, Inc. faucet. Includes a JG 1/4 x 7/16 - 24UNS Speedfit connector, angle stop valve, teflon tape, six feet of 1/4" OD tubing, and installation instructions.